



ativa

# IT107W WIDE



Display	IT107W
Graphic Type	TFT 7" Graphic LCD 65k Colors
Touch screen	Analog Touch Screen
Backlighting	White LED
Minimum lamp life at 25° C	50.000
Resolution pixel h-v (inches)	800 x 480
<b>Processor</b>	
CPU	Intel PXA 270 520 MHz
<b>System Memory</b>	
RAM (byte)	64M
Flash (byte)	32M
<b>Interfaces</b>	
First integrated port	SP1 (232/485/MPI)
Second integrated port	SP2 (232/485/MPI), CAN, Profibus-DP
USB port Host	1 x v 1.1
USB port Device	1 x v 1.1
Card Bus Slot (for Secure Digital/MMC)	Secure Digital
<b>Networks</b>	
Integrated (on all models)	Ethernet 10/100 Mbit - Rj45
<b>Dimensions</b>	
External (W x H x D) (mm)	202 x 142 x 39,2 (SP1) 58,2 (SP1-SP2)
Bore holes (W x H) (mm)	194 x 134
<b>Clock</b>	
Supercapacitor Hardware Clock	Supercapacitor 72h
<b>Technical specification</b>	
Power supply	18...32 Vdc
Power consumption (24 Vdc)	~ 8 W
Protection level	IP 65 front
Working temperature (°C)	0...+50
Storage/transport temperature (°C)	-20...+60
Humidity (non-condensing)	85%
Weight (Kg)	~ 1,6